

CLAIMS

1. Multi-carrier communication system wherein data are transferred bi-directionally in a time division duplexed way, and
5 wherein a first pilot carrier whose instantaneous frequency is a fraction of a sample rate of a first transceiver (VDSL_LT) and which is orthogonal to other carriers used in said multi-carrier communication system, is transferred to enable a second transceiver (VDSL_NT) to recover said sample rate,

10 CHARACTERISED IN THAT a second pilot carrier whose mean frequency is a fraction of a time division duplexing frame rate and which is orthogonal to other carriers used in said multi-carrier communication system, is transferred from said first transceiver (VDSL_LT) to said second transceiver (VDSL_NT) to enable said
15 second transceiver (VDSL_NT) to recover said time division duplexing frame rate, said second pilot carrier being different from said first pilot carrier.

2. Multi-carrier communication system according to claim 1,
20 CHARACTERISED IN THAT said first pilot carrier is constituted by interpolating a plurality of carriers.

3. Multi-carrier communication system according to claim 1 or claim 2,
25 CHARACTERISED IN THAT said first pilot carrier and/or said second pilot carrier are/is randomised.

4. Multi-carrier communication system according to claim 1 or claim 2,

5. Multi-carrier transmitter (VDSL_LT) suitable for use in a time division duplexing system, said multi-carrier transmitter (VDSL_LT) comprising:

- CHARACTERISED IN THAT said multi-carrier transmitter (VDSL_LT)
15 further comprises:

- d. second pilot carrier transmission means, coupled to said second pilot carrier generation means (ROT, IFFT, T/S, DAC, PLL) and adapted to transmit said second pilot carrier.

6. Multi-carrier receiver (VDSL_NT) suitable for use in a time division duplexing system, said multi-carrier receiver (VDSL_NT) comprising:

- M. Peeters**

frequency is a fraction of a transmitter sample rate and which is orthogonal to other carriers received by said multi-carrier receiver (VDSL_NT),

CHARACTERISED IN THAT said multi-carrier receiver (VDSL_NT)

5 further comprises:

- b. second pilot carrier receiving means (ADC, S/D, FFT, ROT2, ROT1, PLL1, PLL2), adapted to receive a second pilot carrier whose mean frequency is a fraction of a time division duplexing frame rate and which is orthogonal to other carriers received by said multi-carrier receiver (VDSL_NT), said second pilot carrier being different
- 10 from said first pilot carrier.

120308 AN - AP - 05/04/2001 - p. 16/17